

http://www.glaciallight.com


7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,

Operator  
 Telephone +886 2 2244-1227  
 Fax +886 2 2244-1241  
 e-Mail sales@GlacialLight.com

## GlacialLight GL-CFD06DA-35C-CW-5000K-45D-frosted glass / Luminaire Data Sheet

Luminous emittance 1:

See our luminaire catalog for an image of the luminaire.



Luminaire classification according to CIE: 100  
 CIE flux code: 78 93 98 100 101

Luminous emittance 1:

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	16.5	17.4	16.8	17.6	17.8	16.2	17.1	16.5	17.3	17.5
	3H	16.9	17.8	17.2	18.0	18.3	16.7	17.5	17.0	17.7	18.0
	4H	17.1	17.9	17.4	18.1	18.4	16.8	17.6	17.1	17.8	18.1
	6H	17.1	17.9	17.5	18.1	18.4	16.9	17.6	17.2	17.9	18.2
	8H	17.2	17.8	17.5	18.1	18.4	16.9	17.6	17.2	17.9	18.2
4H	12H	17.1	17.8	17.5	18.1	18.4	16.9	17.5	17.2	17.8	18.2
	2H	16.7	17.4	17.0	17.7	18.0	16.4	17.2	16.7	17.5	17.7
	3H	17.2	17.9	17.6	18.2	18.5	17.0	17.7	17.4	18.0	18.3
	4H	17.5	18.0	17.8	18.4	18.7	17.2	17.8	17.6	18.1	18.5
	6H	17.6	18.1	18.0	18.4	18.8	17.4	17.8	17.8	18.2	18.6
8H	8H	17.6	18.0	18.0	18.4	18.8	17.4	17.8	17.8	18.2	18.6
	12H	17.6	18.0	18.1	18.4	18.8	17.4	17.8	17.8	18.2	18.6
	4H	17.5	17.9	17.9	18.3	18.7	17.3	17.7	17.7	18.1	18.5
	6H	17.7	18.0	18.1	18.4	18.9	17.5	17.8	17.9	18.2	18.7
	8H	17.7	18.0	18.2	18.5	18.9	17.5	17.8	18.0	18.3	18.7
12H	12H	17.7	18.0	18.2	18.5	19.0	17.5	17.8	18.0	18.3	18.8
	4H	17.5	17.9	17.9	18.3	18.7	17.3	17.6	17.7	18.1	18.5
	6H	17.7	18.0	18.1	18.4	18.9	17.5	17.8	17.9	18.2	18.7
8H	17.7	18.0	18.2	18.4	18.9	17.5	17.8	18.0	18.2	18.7	
Variation of the observer position for the luminaire distances S											
S = 1.0H	+1.2 / -1.2					+1.1 / -1.1					
S = 1.5H	+2.7 / -1.9					+2.5 / -1.9					
S = 2.0H	+4.3 / -2.6					+4.0 / -2.5					
Standard table	BK02					BK02					
Correction Summand	-0.3					-0.5					
Corrected Glare Indices referring to 2450lm Total Luminous Flux											


<http://www.glaciallight.com>

7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,

Operator  
Telephone +886 2 2244-1227  
Fax +886 2 2244-1241  
e-Mail [sales@GlacialLight.com](mailto:sales@GlacialLight.com)

### GlacialLight GL-CFD06DA-35C-CW-5000K-45D-frosted glass / LDC (Polar)

Luminaire: GlacialLight GL-CFD06DA-35C-CW-5000K-45D-frosted glass  
Lamps: 1 x Feature Light




<http://www.glaciallight.com>

7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,

Operator  
Telephone +886 2 2244-1227  
Fax +886 2 2244-1241  
e-Mail [sales@GlacialLight.com](mailto:sales@GlacialLight.com)

### GlacialLight GL-CFD06DA-35C-CW-5000K-45D-frosted glass / LDC (Linear)

Luminaire: GlacialLight GL-CFD06DA-35C-CW-5000K-45D-frosted glass  
Lamps: 1 x Feature Light



http://www.glaciallight.com

7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,

Operator  
 Telephone +886 2 2244-1227  
 Fax +886 2 2244-1241  
 e-Mail sales@GlacialLight.com

**GlacialLight GL-CFD06DA-35C-CW-5000K-45D-frosted glass / UGR-Table**

Luminaire: GlacialLight GL-CFD06DA-35C-CW-5000K-45D-frosted glass  
 Lamps: 1 x Feature Light

<b>Glare Evaluation According to UGR</b>											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X      Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	16.5	17.4	16.8	17.6	17.8	16.2	17.1	16.5	17.3	17.5
	3H	16.9	17.8	17.2	18.0	18.3	16.7	17.5	17.0	17.7	18.0
	4H	17.1	17.9	17.4	18.1	18.4	16.8	17.6	17.1	17.8	18.1
	6H	17.1	17.9	17.5	18.1	18.4	16.9	17.6	17.2	17.9	18.2
	8H	17.2	17.8	17.5	18.1	18.4	16.9	17.6	17.2	17.9	18.2
	12H	17.1	17.8	17.5	18.1	18.4	16.9	17.5	17.2	17.8	18.2
4H	2H	16.7	17.4	17.0	17.7	18.0	16.4	17.2	16.7	17.5	17.7
	3H	17.2	17.9	17.6	18.2	18.5	17.0	17.7	17.4	18.0	18.3
	4H	17.5	18.0	17.8	18.4	18.7	17.2	17.8	17.6	18.1	18.5
	6H	17.6	18.1	18.0	18.4	18.8	17.4	17.8	17.8	18.2	18.6
	8H	17.6	18.0	18.0	18.4	18.8	17.4	17.8	17.8	18.2	18.6
	12H	17.6	18.0	18.1	18.4	18.8	17.4	17.8	17.8	18.2	18.6
8H	4H	17.5	17.9	17.9	18.3	18.7	17.3	17.7	17.7	18.1	18.5
	6H	17.7	18.0	18.1	18.4	18.9	17.5	17.8	17.9	18.2	18.7
	8H	17.7	18.0	18.2	18.5	18.9	17.5	17.8	18.0	18.3	18.7
	12H	17.7	18.0	18.2	18.5	19.0	17.5	17.8	18.0	18.3	18.8
12H	4H	17.5	17.9	17.9	18.3	18.7	17.3	17.6	17.7	18.1	18.5
	6H	17.7	18.0	18.1	18.4	18.9	17.5	17.8	17.9	18.2	18.7
	8H	17.7	18.0	18.2	18.4	18.9	17.5	17.8	18.0	18.2	18.7
Variation of the observer position for the luminaire distances S											
S = 1.0H		+1.2 / -1.2					+1.1 / -1.1				
S = 1.5H		+2.7 / -1.9					+2.5 / -1.9				
S = 2.0H		+4.3 / -2.6					+4.0 / -2.5				
Standard table		BK02					BK02				
Correction Summand		-0.3					-0.5				
Corrected Glare Indices referring to 2450lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.

http://www.glaciallight.com

7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,

Operator  
 Telephone +886 2 2244-1227  
 Fax +886 2 2244-1241  
 e-Mail sales@GlacialLight.com

## GlacialLight GL-CFD06DA-35C-CW-5000K-45D-frosted glass / Glare Data Sheet

Luminaire: GlacialLight GL-CFD06DA-35C-CW-5000K-45D-frosted glass

Lamps: 1 x Feature Light

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	16.5	17.4	16.8	17.6	17.8	16.2	17.1	16.5	17.3	17.5
	3H	16.9	17.8	17.2	18.0	18.3	16.7	17.5	17.0	17.7	18.0
	4H	17.1	17.9	17.4	18.1	18.4	16.8	17.6	17.1	17.8	18.1
	6H	17.1	17.9	17.5	18.1	18.4	16.9	17.6	17.2	17.9	18.2
	8H	17.2	17.8	17.5	18.1	18.4	16.9	17.6	17.2	17.9	18.2
	12H	17.1	17.8	17.5	18.1	18.4	16.9	17.5	17.2	17.8	18.2
4H	2H	16.7	17.4	17.0	17.7	18.0	16.4	17.2	16.7	17.5	17.7
	3H	17.2	17.9	17.6	18.2	18.5	17.0	17.7	17.4	18.0	18.3
	4H	17.5	18.0	17.8	18.4	18.7	17.2	17.8	17.6	18.1	18.5
	6H	17.6	18.1	18.0	18.4	18.8	17.4	17.8	17.8	18.2	18.6
	8H	17.6	18.0	18.0	18.4	18.8	17.4	17.8	17.8	18.2	18.6
	12H	17.6	18.0	18.1	18.4	18.8	17.4	17.8	17.8	18.2	18.6
8H	4H	17.5	17.9	17.9	18.3	18.7	17.3	17.7	17.7	18.1	18.5
	6H	17.7	18.0	18.1	18.4	18.9	17.5	17.8	17.9	18.2	18.7
	8H	17.7	18.0	18.2	18.5	18.9	17.5	17.8	18.0	18.3	18.7
	12H	17.7	18.0	18.2	18.5	19.0	17.5	17.8	18.0	18.3	18.8
12H	4H	17.5	17.9	17.9	18.3	18.7	17.3	17.6	17.7	18.1	18.5
	6H	17.7	18.0	18.1	18.4	18.9	17.5	17.8	17.9	18.2	18.7
	8H	17.7	18.0	18.1	18.4	18.9	17.5	17.8	17.9	18.2	18.7
	8H	17.7	18.0	18.2	18.4	18.9	17.5	17.8	18.0	18.2	18.7
Variation of the observer position for the luminaire distances S											
S = 1.0H	+1.2 / -1.2					+1.1 / -1.1					
S = 1.5H	+2.7 / -1.9					+2.5 / -1.9					
S = 2.0H	+4.3 / -2.6					+4.0 / -2.5					
Standard table	BK02					BK02					
Correction Summand	-0.3					-0.5					
Corrected Glare Indices referring to 2450lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.

