


<http://www.glaciallight.com>

 7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,  
Taiwan, 235, R.O.C.

 Operator  
Telephone +886 2 2244-1227  
Fax +886 2 2244-1241  
e-Mail sales@GlacialLight.com

## GlacialLight GL-FL55-NW-4000K-60D Lens-with lampshade / Luminaire Data Sheet

Luminous emittance 1:

 See our luminaire catalog for an image of the  
luminaire.

 Luminaire classification according to CIE: 100  
CIE flux code: 99 99 100 100 103


Luminous emittance 1:

Glare Evaluation According to UGR										
		70	70	50	50	30	70	70	50	50
p Ceiling		70	70	50	50	30	70	70	50	50
p Walls		50	50	50	50	30	50	50	50	30
p Floor		20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis			
2H	2H	15.3	15.9	15.5	15.1	15.7	14.6	15.3	14.9	15.5
	3H	15.1	15.7	15.4	15.0	15.2	14.5	15.1	14.8	15.3
	4H	15.1	15.6	15.4	15.0	15.1	14.5	15.0	14.8	15.3
	5H	15.0	15.5	15.4	15.0	15.1	14.4	14.9	14.7	15.2
	12H	15.0	15.5	15.3	15.0	15.1	14.4	14.9	14.7	15.1
4H	2H	15.1	15.6	15.4	15.0	15.1	14.4	15.0	14.7	15.2
	3H	14.9	15.4	15.3	15.0	15.0	14.3	14.8	14.7	15.1
	4H	14.9	15.3	15.3	15.0	15.0	14.3	14.7	14.6	15.0
	5H	14.9	15.2	15.3	15.0	15.0	14.2	14.6	14.6	14.9
	12H	14.8	15.1	15.3	15.0	15.0	14.2	14.5	14.6	14.9
5H	2H	14.8	15.1	15.3	15.0	15.0	14.2	14.4	14.6	14.8
	3H	14.8	15.0	15.2	15.4	15.0	14.1	14.3	14.6	14.7
	4H	14.7	14.9	15.2	15.4	15.0	14.1	14.3	14.6	14.7
	5H	14.8	14.9	15.2	15.4	15.0	14.1	14.2	14.6	14.7
	12H	14.8	14.9	15.2	15.4	15.0	14.1	14.2	14.6	14.7
12H	2H	14.8	15.0	15.2	15.4	15.0	14.1	14.4	14.6	14.8
	3H	14.7	14.9	15.2	15.3	15.0	14.1	14.2	14.5	14.7
	4H	14.7	14.9	15.2	15.3	15.0	14.1	14.2	14.5	14.7
	5H	14.7	14.9	15.2	15.3	15.0	14.1	14.2	14.5	14.7
	12H	14.7	14.9	15.2	15.3	15.0	14.1	14.2	14.5	14.7
Variation of the observer position for the luminaire distance S										
S = 1.0H		+8.1 / -9.5					+8.0 / -10.0			
S = 1.5H		+6.9 / -9.8					+6.9 / -10.8			
S = 2.0H		+10.9 / -10.5					+10.9 / -11.0			
Standard table		5000					5000			
Correction Summand		-3.2					-3.9			
Corrected Glare Indices referring to 5000lm Total Luminous Flux										

<http://www.glaciallight.com>7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,  
Taiwan, 235, R.O.C.Operator  
Telephone +886 2 2244-1227  
Fax +886 2 2244-1241  
e-Mail [sales@GlacialLight.com](mailto:sales@GlacialLight.com)**GlacialLight GL-FL55-NW-4000K-60D Lens-with lampshade / LDC (Polar)**

Luminaire: GlacialLight GL-FL55-NW-4000K-60D Lens-with lampshade


Lamps: 1 x Flood Light



<http://www.glaciallight.com>7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,  
Taiwan, 235, R.O.C.Operator  
Telephone +886 2 2244-1227  
Fax +886 2 2244-1241  
e-Mail [sales@GlacialLight.com](mailto:sales@GlacialLight.com)**GlacialLight GL-FL55-NW-4000K-60D Lens-with lampshade / LDC (Linear)**

Luminaire: GlacialLight GL-FL55-NW-4000K-60D Lens-with lampshade

Lamps: 1 x Flood Light



<http://www.glaciallight.com>

 7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,  
Taiwan, 235, R.O.C.

 Operator  
Telephone +886 2 2244-1227  
Fax +886 2 2244-1241  
e-Mail [sales@GlacialLight.com](mailto:sales@GlacialLight.com)

## GlacialLight GL-FL55-NW-4000K-60D Lens-with lampshade / UGR-Table

Luminaire: GlacialLight GL-FL55-NW-4000K-60D Lens-with lampshade

Lamps: 1 x Flood Light

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X            Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	15.3	15.9	15.5	16.1	16.3	14.6	15.3	14.9	15.5	15.7
	3H	15.1	15.7	15.4	16.0	16.2	14.5	15.1	14.8	15.3	15.6
	4H	15.1	15.6	15.4	15.9	16.1	14.5	15.0	14.8	15.3	15.5
	6H	15.0	15.5	15.4	15.8	16.1	14.4	14.9	14.7	15.2	15.5
	8H	15.0	15.5	15.3	15.8	16.1	14.4	14.9	14.7	15.1	15.4
	12H	15.0	15.5	15.3	15.8	16.1	14.3	14.8	14.7	15.1	15.4
4H	2H	15.1	15.6	15.4	15.9	16.1	14.4	15.0	14.7	15.2	15.5
	3H	14.9	15.4	15.3	15.7	16.0	14.3	14.8	14.7	15.1	15.4
	4H	14.9	15.3	15.3	15.6	16.0	14.3	14.7	14.6	15.0	15.3
	6H	14.9	15.2	15.3	15.5	15.9	14.2	14.5	14.6	14.9	15.3
	8H	14.8	15.1	15.3	15.5	15.9	14.2	14.5	14.6	14.9	15.3
	12H	14.8	15.1	15.3	15.5	15.9	14.2	14.4	14.6	14.8	15.2
8H	4H	14.8	15.1	15.2	15.5	15.9	14.2	14.4	14.6	14.8	15.2
	6H	14.8	15.0	15.2	15.4	15.8	14.1	14.3	14.6	14.7	15.2
	8H	14.7	14.9	15.2	15.4	15.8	14.1	14.3	14.6	14.7	15.2
	12H	14.8	14.9	15.2	15.4	15.9	14.1	14.2	14.6	14.7	15.2
12H	4H	14.8	15.0	15.2	15.4	15.8	14.1	14.4	14.5	14.8	15.2
	6H	14.7	14.9	15.2	15.3	15.8	14.1	14.2	14.5	14.7	15.2
	8H	14.7	14.9	15.2	15.3	15.8	14.1	14.2	14.5	14.7	15.2
Variation of the observer position for the luminaire distances S											
S = 1.0H		+6.1 / -9.5					+6.0 / -10.0				
S = 1.5H		+8.9 / -9.8					+8.9 / -10.6				
S = 2.0H		+10.9 / -10.5					+10.9 / -11.0				
Standard table		BK00					BK00				
Correction Summand		-3.2					-3.9				
Corrected Glare Indices referring to 6250lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117    Spacing-to-Height-Ratio = 0.25.

<http://www.glaciallight.com>

 7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,  
Taiwan, 235, R.O.C.

 Operator  
Telephone +886 2 2244-1227  
Fax +886 2 2244-1241  
e-Mail sales@GlacialLight.com

## GlacialLight GL-FL55-NW-4000K-60D Lens-with lampshade / Glare Data Sheet

 Luminaire: GlacialLight GL-FL55-  
NW-4000K-60D Lens-with  
lampshade

Lamps: 1 x Flood Light

Glare Evaluation According to UGR												
p Ceiling	70	70	50	50	30	70	70	50	50	30		
p Walls	50	30	50	30	30	50	30	50	30	30		
p Floor	20	20	20	20	20	20	20	20	20	20		
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	15.3	15.9	15.5	16.1	16.3	14.6	15.3	14.9	15.5	15.7	
	3H	15.1	15.7	15.4	16.0	16.2	14.5	15.1	14.8	15.3	15.6	
	4H	15.1	15.6	15.4	15.9	16.1	14.5	15.0	14.8	15.3	15.5	
	6H	15.0	15.5	15.4	15.8	16.1	14.4	14.9	14.7	15.2	15.5	
	8H	15.0	15.5	15.3	15.8	16.1	14.4	14.9	14.7	15.1	15.4	
	12H	15.0	15.5	15.3	15.8	16.1	14.3	14.8	14.7	15.1	15.4	
4H	2H	15.1	15.6	15.4	15.9	16.1	14.4	15.0	14.7	15.2	15.5	
	3H	14.9	15.4	15.3	15.7	16.0	14.3	14.8	14.7	15.1	15.4	
	4H	14.9	15.3	15.3	15.6	16.0	14.3	14.7	14.6	15.0	15.3	
	6H	14.9	15.2	15.3	15.5	15.9	14.2	14.5	14.6	14.9	15.3	
	8H	14.8	15.1	15.3	15.5	15.9	14.2	14.5	14.6	14.9	15.3	
	12H	14.8	15.1	15.3	15.5	15.9	14.2	14.4	14.6	14.8	15.2	
8H	4H	14.8	15.1	15.2	15.5	15.9	14.2	14.4	14.6	14.8	15.2	
	6H	14.8	15.0	15.2	15.4	15.8	14.1	14.3	14.6	14.7	15.2	
	8H	14.7	14.9	15.2	15.4	15.8	14.1	14.3	14.6	14.7	15.2	
	12H	14.8	14.9	15.2	15.4	15.9	14.1	14.2	14.6	14.7	15.2	
12H	4H	14.8	15.0	15.2	15.4	15.8	14.1	14.4	14.5	14.8	15.2	
	6H	14.7	14.9	15.2	15.3	15.8	14.1	14.2	14.5	14.7	15.2	
	8H	14.7	14.9	15.2	15.3	15.8	14.1	14.2	14.5	14.7	15.2	
Variation of the observer position for the luminaire distances S												
S = 1.0H	+6.1 / -9.5					+6.0 / -10.0						
S = 1.5H	+8.9 / -9.8					+8.9 / -10.6						
S = 2.0H	+10.9 / -10.5					+10.9 / -11.0						
Standard table	BK00					BK00						
Correction Summand	-3.2					-3.9						
Corrected Glare Indices referring to 6250lm Total Luminous Flux												

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.

